

SRCC SPORTS 2000 CHAMPIONSHIP

SPORTING & TECHNICAL REGULATIONS 2006

1. SPORTING REGULATIONS-GENERAL.

1.1 TITLE & JURISDICTION:

1.1.1 The Sports 2000 Championship is organised and administered by the Sports 2000 Racing Car Club (SRCC) in accordance with the General Regulations the Royal Automobile Club Motor Sports Association (incorporating the provisions of the International Sporting Code of the FIA and these Championship Regulations.

1.1.2 The Organisers reserve the right to issue additional statements clarifying items in the rules and regulations, and all such statements will be issued to all registered drivers by posting to the address detailed on the registration form (subject to MSA Regulation B.8.4c).

MSA Championship Permit No:

Race Status: National B.

MSA Championship Grade: C

1.2 OFFICIALS:

1.2.1 Co-ordinator: Carol Glenn. 63 Boyne Road, London, SE14 5AN. Phone No. 07790740696
e-mail carollglenn@hotmail.com

1.2.2 Eligibility Scrutineer: John Atkinson, 23 Dale Road, Dunstable, Beds LU5 4PY. (01582 603973)
Mick Mobberley, Hi-Tech Motorsport, Lodge Forge Trading Estate, Cradley Road, Cradley Heath, West Midlands. Phone No. 1384 561777

1.2.3 Championship Stewards: John Ward, Steve Mills, & Roy Bates.
In the event of any of the Championship Stewards listed above being unavailable or being unable to consider any particular matter due to a perceived conflict of interest, the organisers reserve the right to appoint an alternative Championship Steward or, if deemed to be necessary, more than one alternative Championship Steward.

1.2.4 Championship Clerk of Course: David Pierre Phone No 078891 77729 Fax 0121 3507029 e-mail david.pierre@hae.org.uk

1.3 COMPETITOR ELIGIBILITY:

1.3.1 Entrants must be fully paid up valid membership card holding members of the SRCC and in possession of valid 2006 MSA Entrants Licences.

1.3.2 Drivers and Entrant Drivers must be fully paid up valid membership card holding members of the BRSCC, be registered for the Championship and be in possession of a valid MSA Competition (Racing) National (B) or above licences.

Or as the events have been inscribed on the FIA "National Event Authorised Foreign Participation" (NEAFP) Calendar Non MSA licence holders (E2.21.4.) will be deemed "Guest Drivers" (SEE 1.6.5).

1.3.3 All necessary documentation must be presented for checking at all rounds when signing-on.

1.4 REGISTRATION:

1.4.1 All drivers must register as competitors for the championship by returning the Registration Form with the Registration Fee to the General Secretary (SRCC) prior to the Final Closing date for the first round being entered.

1.4.2 The Registration Fee is £150 made payable to The SRCC.

1.4.3 Registrations will be accepted from 1st January 2006 until the closing date for the last round of the Championship.

1.4.4 Registration numbers will be the permanent Competition numbers for the Championship.

1.5 CHAMPIONSHIP ROUNDS:

The Sports 2000 Duratec Championship will be contested over 8 rounds at the following venues:

DATE	CIRCUIT
April 15 th	Brands Hatch GP
May 27 th	Oulton Park International
June 17/18 th	Donington Park
July 8/9 th	Snetterton
August 12/13 th	Rockingham
September 9 th	Silverstone GP
September 30/Oct 1 st	Thruxton
October 21/22 nd	Brands Hatch

1.6 SCORING:

1.6.1 Points will be awarded to Competitors listed as classified finishers in the Final Results as follows:
1st-15; 2nd-14; 3rd-13; 4th-12; 5th-11; 6th-10; 7th-9; 8th-8; 9th-7; 10th-6; 11th-5; 12th-4; 13th-3; 14th-2; 15th- and all other qualifiers-1 point.

1.6.2 The totals from all qualifying rounds less 1 (one) will determine the final championship points and positions.

1.6.3 Ties shall be resolved using the formula in J 3.4 of the 2006 MSA Yearbook

1.6.4 Should a combined race for the Sports 2000 Duratec and Sports 2000 Championships be run, there will be a single qualifying session, with the single combined grid based on the fastest qualifying times. A single results sheet will be published but points will be awarded separately, in accordance with the individual championship regulations to cars competing in the Duratec Championship and the Sports 2000 Championship. Thus the first car in each class will receive 15 points, the second car in each class 14 points, the third car in each class 13 points and so on down to 14th receiving 2 points with all other qualifiers, 1 point.

1.6.5 The organisers reserve the right to invite "Guest Drivers" to take part in any round or number of rounds, however these drivers will not be eligible to score Championship points in any event they take part in.

1.7 AWARDS:

1.7.1 All awards are to be provided by the Organising Club unless agreed otherwise.

1.7.2 Per Round: Garlands to 1st in each class. Trophies to 1st, 2nd, and 3rd overall and also in each Class.

- 1.7.3 Championship: Trophies to 1st, 2nd, 3rd, 4th and 5th in each Class.
- 1.7.4 Bonuses: Per Round: Not applicable. Championship: Not applicable.
- 1.7.5 Presentations: Garlands and Trophies are to be provided for presentation at the end of each race or at an end of the meeting presentation ceremony.
- 1.7.6 Entertainment Tax Liability: Not applicable.
- 1.7.7 Title to all Trophies: In the event of any Provisional Results or Championship Tables being revised after any provisional presentations and such revisions affect the distribution of any awards the Competitors concerned must return such awards to the SRCC in good condition within 7days.

2 SPORTING REGULATIONS – JUDICIAL PROCEDURES

- 2.1 **ROUNDS:** In accordance with Section O of the **2006** MSA Yearbook.
- 2.2 **CHAMPIONSHIP:** In accordance with Section O of the **2006** MSA Yearbook.

3 SPORTING REGULATIONS - CHAMPIONSHIP RACE MEETINGS & RACE PROCEDURES

3.1 ENTRIES:

- 3.1.1 Competitors are responsible for sending in correct and complete entries with the correct entry fees prior to the entry closing dates as per the entry forms for each round.
- 3.1.2 Incorrect or incomplete entries (including driver to be nominated entries) are to be held in abeyance until they are complete and correct and the date of receipt for acceptance of entry purposes shall be the date on which the Secretary of the Meeting receives the missing or corrected information or fee.
- 3.1.3 Any withdrawal of Entry or Driver/Car changes made after acceptance of any entry must be notified to the Secretary of the Meeting in writing. If Driver/Vehicle changes are made after the publication of Entry Lists with Final Instructions, the Competitor concerned must apply for approval of acceptance by the Stewards of the Meeting BEFORE Signing-On.
- 3.1.4 The maximum entry fee for each round shall be as per the Supplementary Regulations for each round.
- 3.1.5 The SRCC General Secretary maintains a selection order list. Entries up to the maximum number permitted to practice will be selected according to the list current on the closing day, the selection for the race will be made from these entries in order of receiving them. Any entries in excess of this will be treated as Reserves in order of their standing on the aforementioned list. If on the closing date, entries accepted in accordance with the above have reached or exceeded the maximum number permitted to practice, any further entries will be held in abeyance.
- 3.1.6 Reserves are to be nominated on the Final List of Entries published with the Final Instructions or Amendment Sheet Bulletins. All Reserves will practice and replace withdrawn or retired entries in Reserve Number order irrespective of class subject to the provisions of 3.4. If Reserves are given Grid Places prior to issue of the first Grid Sheets for any round, the times set in Practice shall determine their grid positions. If Reserves are given places after the publication of the grid sheet and prior to cars being collected in the official 'Assembly Area' they will be placed at the rear of the grid and be started without any time delay. Otherwise, they will be held in the Pit lane and be released to start the race after the last car to start the GREEN FLAG LAP or last car to take the start has passed the startline or pit lane exit, whichever is the later. Such approval to start MUST be obtained from the Clerk of the Course.

- 3.2 **BRIEFINGS:** Organisers should notify Competitors of the times and locations for all briefings in the Final Instructions for the meetings. Competitors must attend all briefings.

3.3 PRACTICE:

- 3.3.1 The minimum period of practice to be 20 minutes. Should any practice session be disrupted, the Clerk of the Course shall not be obliged to resume the session or re-run sessions to achieve the championship criteria and the decision of the Clerk of the Course shall be final.
- 3.3.2 Should the need arise to stop any practice, RED LIGHTS will be switched on at the Start Line and RED FLAGS will be displayed at the Start Line and at all other Marshal signalling points around the circuit. This is the signal for all drivers to cease circulating at racing speeds, to slow to a safe and reasonable pace and return to the pit lane unless directed by officials, not to do so.
- 3.4 **QUALIFICATION:** Each driver should complete a minimum of 3 laps practice in the car to be raced and in the correct session in order to qualify for selection and order of precedence as set out in the MSA regulations J4.4. However the Organisers reserve the right to select a championship contender, who has failed to qualify under the above requirements, ahead of a reserve that is not in contention for championship honours. The Clerk of the Course and/or Stewards of the Meeting shall have the right to exclude any driver whose practice times or driving are considered to be unsatisfactory - as per MSA Regulation J 4.4.3.

3.5 RACES:

- 3.5.1 The standard minimum scheduled race distance shall be 25 minutes. Should any race distance be reduced at the discretion of the Clerk of the Course or Stewards of the Meeting, it shall still count as a full points-scoring round. The procedure for qualification races is specified in 3.13

3.6 STARTS:

- 3.6.1 All race start countdowns are to have a minimum elapsed period of 3 minutes from the time all cars are released to form up on the grid to the start of the Green Flag Lap(s) in the formation as specified on the Track Licence for each circuit.
- 3.6.2 The minimum countdown procedures/audible warnings sequence shall be - 1 minute to start of Green Flag/Pace Lap - Start Engines/Clear Grid. 30 seconds-Visible and audible warning for start of Green Flag/Pace Lap.
- 3.6.3 The use of tyre heating/heat retention devices, tyre treatments and compounds is prohibited.
- 3.6.4 Any cars removed from the grid after the 1 minute stage or driven into the pits on the Green Flag Lap shall be held in the pit lane and may start the race after the last car to take the start from the grid has passed the startline or pit exit lane whichever is the later.
- 3.6.5 Any drivers unable to start the Green Flag/Pace lap or start are required to indicate their situation as per MSA regulation J 13.10.2. and any drivers unable to maintain grid positions on the Green Flag Lap to the extent that ALL other cars are ahead of them, may complete the Green Flag Lap but MUST remain at the rear of the last row of the grid but ahead of any cars to be started with a time delay.
- 3.6.6 Excessive weaving to warm-up tyres - using more than 50% of the track width, and falling back in order to accelerate and practice starts, is prohibited.
- 3.6.7 A five second board will be used to indicate that the grid is complete The red lights will be switched on five seconds after the board is withdrawn. All cars will start racing when the red start light(s) are extinguished. In the event of any starting lights failure the Starter will revert to the use of the National flag.

3.7 RACE STOPS:

- 3.7.1 Should the need arise to stop any race, RED LIGHTS will be switched on at the Startline and RED FLAGS will be displayed at the Startline and

at all Marshals Signalling Points around the circuit. This is a signal for all drivers to cease circulating at racing speeds, to slow to a safe and reasonable pace and to return to the starting grid area, which will automatically become a Parc Ferme area. Cars may not enter the Pits unless directed to do so. Work on cars already in the Pits must cease when a race is stopped.

- 3.7.2 Case A – Less than two laps completed by Race leader.
The Race will be null and void. The race will restart from the original grid positions. Competitors unable to take the restart may be replaced by reserves who will start from the back of the grid in reserve order. Gaps on the grid should not be closed up. The length of the restarted race will be determined by the Clerk of the Course.
- 3.7.3 Case B – More than two laps completed by Race Leader but less than 50%
The Race will restart from a grid set out by the finishing order of part one (as per J5.4.4). The result of the race will be the finishing order at the end of part two. The length of the restarted race will be determined by the Clerk of the Course.
- 3.7.4 If the leader has completed more than half of the race distance or duration it shall not be re-started and the results will be declared in accordance with MSA Regulation J.5.4.4.
- 3.8 RE-SCRUTINY:** All vehicles reported involved in contact incidents during races or practice must be re-presented to the Scrutineers before continuing in the races or practice.
- 3.9 PITS AND PITLANE SAFETY:**
- 3.9.1 Pits: Entrants must ensure that the MSA, Circuit Management and Organising Club Safety Regulations are complied with at all times.
- 3.9.2 Pitlane: The outer lane or lanes are to be kept unobstructed to allow safe passage of cars at all times. The onus shall be on all Drivers to take all due care and drive at minimum speeds in pit lanes.
- 3.9.3 Refuelling: May only be carried out in accordance with the MSA J. 14 Regulations, Circuit Management Regulations and the SRs or Final Instructions issued for each Circuit/Meeting.
- 3.9.4 There will be a speed limit of 60 kph within the marked pit lane that will be checked by radar. You may be penalised for exceeding that speed.
- 3.10 RACE FINISHES:** After taking the chequered flag drivers are required to: - Progressively and safely slow down, remain behind any competitors ahead of them, return to the Pit lane Entrance/Paddock Entrance as instructed, comply with any directions given by Marshals or Officials and to keep their helmets on and harnesses done up while on the circuit or in the pit lane. NB. After taking the finish all drivers are to take their cars directly to the Scrutineering Bay. The only exception is when they are directed to the award presentation area, by a race official. These cars will be taken directly to the Scrutineering Bay after the presentations without interference from any person. Competitors who fail to comply will be reported to the Clerk of Course.
- 3.11 RESULTS:** All Practice Timesheets, Grid Sheets and Race Results are to be deemed PROVISIONAL until all vehicles are released by Scrutineers after Post Practice/Race Scrutineering and/or after completion of any Judicial or Technical procedures.
- 3.12 TIMING MODULES**
- 3.12.1 All competitors are required to purchase and fit an approved Electronic Self Identification Module (transponder) to their cars for the purposes of accurate timing. It is the responsibility of the competitor to fit these to car in the position and manner specified by the supplier/timing Company. The Modules must be in place and functioning correctly for all Championship qualifying practice sessions and races. The setting and servicing of these items must only be carried out by properly authorised MSA licensed Timekeepers. Competitors are liable for any replacement of the Modules, due to misuse or loss.
- 3.12.2 Competitors may not place electronic timing equipment within 5 metres of the official start, finish or any other official timing lines at any event or test session/day. Any such equipment placed within these zones will be removed.
- 3.13 QUALIFICATION RACES:** Not Applicable
- 3.14 OPERATION OF SAFETY CAR:**
- 3.14.1 The Safety Car may be brought into operation to neutralise a race upon the decision of Clerk of the Course It will be used only if other competitors, or Officials are in immediate physical danger, but the circumstances are not such as to necessitate stopping the race.
- 3.14.2 When the order is given to deploy the Safety Car during the race, stationary yellow flags and "SC" boards will be displayed at the start/finish line and at all Flag Posts. These will be maintained until the intervention is over.
- 3.14.3 During the race, the Safety Car with its revolving yellow lights on will start from the stand-by position and will join the track regardless of where the race leader is. All the competing cars will form up in line behind the "Safety Car" no more than 5 car lengths apart. All overtaking is forbidden unless a car is signalled to do so from the Safety Car.
- 3.14.4 When ordered to do so by the Clerk of the Course the Observer in the Safety Car will, either by use of clear hand signals through the open window of the Safety Car or a fixed green light on the rear of the Safety Car, signal to any cars between it and the race leader that they should pass. These cars will then continue at reduced speed and without overtaking until they reach the line of cars behind the Safety Car.
- 3.14.5 The Safety Car shall be used at least until the leader is behind it and all the remaining competing cars are lined up behind the leader. Once behind the Safety Car, the race leader must keep within 5 car lengths of it and all remaining cars must keep the formation as tight as possible
- 3.14.6 While the Safety Car is in operation, competing cars may stop at their pit, but may only rejoin the track when the green light at the pit lane exit is on. It will be on at all times except when the Safety Car and the line of cars following it are about to pass or are passing the pit exit. A car rejoining the track must proceed at reduced speed until it reaches the end of the line of cars behind the Safety Car.
- 3.14.7 When the Clerk of the Course calls in the Safety Car, it will extinguish all the revolving lights and enter the pits at the end of the lap. As the Safety Car is entering the pits, the flags and "SC" board at the Flag Posts and the "SC" board at the start/finish line will be withdrawn.
- 3.14.8 When the Safety Car has pulled off the circuit and the competing cars are approaching the start/finish line, a waved green flag and/or green light(s) will be shown there. All flag posts will then show a green flag. Overtaking remains strictly forbidden until the competing cars pass the waved green flag and/or green light(s) at the start/finish line. The green flags will be withdrawn after one lap.
- 3.14.9 Each lap completed while the Safety Car is in use will be counted as a race lap.
- 4. CHAMPIONSHIP RACE PENALTIES:**
- 4.1 INFRINGEMENT OF TECHNICAL REGULATIONS:**
- 4.1.1 Arising from post practice Scrutineering or Judicial Action: Minimum Penalty: The provisions of MSA Regulations: O.3.3.
- 4.1.2 Arising from post race Scrutineering or Judicial Action: Minimum Penalty: The provisions of MSA Regulations: O.3.5.1(a) and (b).
For infringements deemed to be of a more serious nature the Clerk of the Course and/or Stewards of the Meeting are to invoke the provisions of Regulation O.3.5.1(c).
- 4.2 INFRINGEMENTS OF NON-TECHNICAL MSA REGULATIONS AND THE SPORTING REGULATIONS ISSUED FOR THE CHAMPIONSHIP:**
- 1) As per **2006** MSA Judicial Procedure Regulations. If excluded as per O.2.5, the driver shall count that event as one of the point scoring rounds counting to his total championship score.

- 2) In order to maintain standards of conduct, the Championship Coordinator will monitor all Officials/Observers reports of adverse behaviour at race meetings. If any individual included on two such reports during one racing season he/she will receive written warning from the Championship Coordinator that his/her driving/behaviour is to be specifically observed at future race meetings. Any adverse reports during this period of observation could result in official MSA action and will result in a Championship Stewards' enquiry, with possible loss of Championship points and refusal of further race entries.
- 3) Cars which have sustained severe body damage or whose appearance is judged by the Clerk of Course to be below acceptable standard may be excluded from the grid.

5 TECHNICAL REGULATIONS

5.1 INTRODUCTION:

The following Technical regulations are set out in accordance with the MSA specified format. Vehicles must be in compliance with MSA General Technical & Safety Regulations as per E, J and Q as appropriate. It should be clearly understood that if the following texts do not clearly specify that you can do it you should work on the principle that you cannot. The Eligibility Scrutineer may seal engines and transmissions at any time during the racing season for later inspection. At the time of the inspection, a member of the SRCC Technical Committee may accompany the Eligibility Scrutineer.

5.2 GENERAL DESCRIPTION:

- 5.2.1 The Sports 2000 Pinto Championship is for competitors participating in open Cockpit 2-seater rear engine sports racing car using standard Ford 2000 cc single overhead camshaft 'Pinto' engine with 2-venturi carburettor. Sports 2000 is a restricted class. Therefore any allowable modifications, changes or additions are as stated herein. There are no exceptions. IF IN DOUBT, DON'T. Cars will run in 3 classes: -
- 5.2.2 Class A is for all cars manufactured after 31/12/86. Class B is for cars manufactured after 31/12/82 but before 31/12/86. Class H is for cars built before 31/12/82. Cars competing in classes B and H must be in the specification for such cars in their original year of manufacture. No updating beyond such specification or other modification is permitted except that classes B and H cars may be updated or modified to accord with the latest specification attained by identical models in their year of manufacture, provided that year is still within the relevant class dates. For example, a car manufactured in January 1983 may be updated to the specification of the same model that was still being produced in December 1985. The onus of proof shall be with the competitor/entrant. An SRCC approved Vehicle Identification Paper/Logbook is mandatory for Class H (Historic) Sports 2000 cars competing in the 2007 season. Cars will be able to start the verification process from mid 2006 season onwards following notification from the SRCC Technical Committee.
- 5.2.3 Where a hybrid car, utilising parts from different sources (e.g. chassis from one car. body from another) is entered, the year of manufacture of the later donor car will be used for the purpose of determining in which class the car shall run. Those major components (e.g. chassis, suspension, brakes, gearbox) used from the donor car must conform to 5.2.2 regarding original specification. Hybrid cars are not eligible for class H.

5.3 SAFETY REQUIREMENTS:

The following Articles of MSA Appendix Q Safety Criteria Regulations will apply: - 1. 1.3, 1.5.2 (recommended) or 1.5.4a or 1.4, 1.4.1, 1.4.5; 2.1, 2.1.3, 2.3; 3., 3.1.2a, 3.1.6, 3.2, 3.2.7; 3.2.8; 3.2.9; 3.2.10; 5; 6; 7.1.4; 8; 9; 10; 11; 13; 14.

5.4 GENERAL TECHNICAL REQUIREMENTS & EXCEPTIONS:

5.5 CHASSIS:

- 5.5.1 Unrestricted except that the use of carbon fibre composite structural materials is prohibited. No engine oil or water tubes are permitted within the cockpit. The engine will be mounted upright and aligned fore and aft in the chassis.
- 5.5.2 It is the intent of these rules to minimise the use of ground effects to achieve aerodynamic down force on the vehicle. Thus the chassis and body surfaces which comprise the underside of the car shall not deviate from a flat plane by more than 2.5cm or 1". This deviation may not be used to create an aerodynamic device. For this purpose the underside is defined as being within the rectangular area along the length between the front edge of the front tyres and the rear edge of the rear tyres and across the outside of the front and rear rims. No aerodynamic devices e.g. skirts, body sides etc., shall extend below this surface anywhere on the car to the rear of the front wheels. The area of this surface must extend to the full width of the body, it must be of minimum width 142.24cm over a length of 91.44cm (i.e. there must be a rectangular solid surface of at least 142.24cm measured across the vehicle by at least 91.44cm measured along the longitudinal axis of the vehicle).
- 5.5.3 There must be no stressed part (centre spine/chassis divider/stiffening panel) in the longitudinal section of the chassis structure, between the steering wheel and the seat back and inside of the driver/passenger space, that exceeds in height, 30cm (11.8") above its lowest point
- 5.5.4 Space for 2 seats shall be provided each of at least 40cm (15.75") width and shall be positioned symmetrically about the vehicle's longitudinal axis. There shall be at least 25cm (9.9") wide foot space for the driver measured at the pedals. The passenger space should provide as much seat space, elbowroom, foot and legroom in terms of length, width and height as that of the driver space. Battery boxes and fire extinguishers are permitted in the passenger seat area.

5.6 BODYWORK INCLUDING SPOILERS.

- i) The body shall provide a cockpit for 2 seats and cover all mechanical components including wheels and suspension members except for the exhaust pipe, induction system and camshaft cover which may protrude through the engine cover.
 - ii) Between the front and rear axle lines the body shall:
 - a) Maintain over a minimum of 70% of the length of the wheelbase and over a depth of 20cm (7.9") a minimum body width exceeding the greatest overall width across the tyres less 15cm (5.9").
 - b) Exceed in height the top of the tyres over a width of 50cm (19.7") excepting only cockpit and engine openings. There shall be no gap between the main body and the mudguards, which must comply with MSA vehicle regulations.
 - iii) The cockpit opening seen in plan view shall be symmetrical about the longitudinal axis of the car and shall be large enough for a horizontal rectangle of 80cm (31.5") by 40cm (15.75") to be passed through with its minor axis aligned with the vehicle's longitudinal axis.
 - iv) All ducted air for heat exchangers (water/oil) and brakes shall pass through those heat exchangers or onto those brakes.
 - v) Maximum vehicle length forward of the front axle centreline: 91.5cm (36") (including spoilers), the maximum vehicle length rearward of the rear axle centreline: 115cm (45.5") (including spoilers)
 - vi) Spoilers mounted at the front of the vehicle are permitted. Those spoilers may only be adjusted in a horizontal plane.
 - vii) Windscreens are optional.
- 5.6.1 Modifications Permitted:
 1. General: None in contravention of 5.6.2 below.
 2. Interior: None in contravention of 5.6.2 below.
 3. Exterior: None in contravention of 5.6.2 below.
 4. Silhouette: None in contravention of 5.6.2 below.
 5. Ground Clearance: Cars must comply with MSA regulation E12.19.10.
 - 5.6.2 Modifications Prohibited:
 1. General: The body above the chassis level in the region of the cockpit shall not be reinforced in any way that would complicate or hinder the rescue of the driver.
 2. Interior: No engine oil or water tubes are permitted within the cockpit.

3. Exterior: Adjustable spoilers mounted at the rear of the vehicle shall be in the form of a flat plane and may only be adjusted within +/- 20° of vertical. There must be no gap between these surfaces, or any other spoiler, and the main bodywork. No bodywork/diffuser extension of the underside panel, or support structure for the floor that may be considered to aid down force, is allowed between the inside faces of the rear wheels, from a vertical plane connecting the rear wheel centre points, to the rear extremity of the car. The rear wheel centre points are defined as 'The centre of the axis, about which the rear wheels rotate, while the vehicle is travelling in a forward or rearwards direction'.
4. Silhouette: Maximum height with driver on board excluding safety rollover bar and mirrors shall not exceed at any time 90cm (35.4") measured from the ground.
5. Ground Clearance: See 5.6.1.5 above

5.7 ENGINE

5.7.1 Modifications Permitted: Where Ford Motor Co are no longer able to supply replacement parts, it is acceptable, within these rules, to use parts from other sources so long as they are direct replacements, do not increase the engine performance and have been approved by the SRCC Technical Committee. A direct replacement, in these rules, means the part, and any sub components within the part, will be dimensionally within the original Ford drawing tolerances and otherwise would conform to the relevant Ford material and test specifications. The only permitted engine is the Ford 2 litre single overhead camshaft 'Pinto' engine.

- a) Cylinder bores may be increased in size by no more than a + 0.5mm rebore on the standard 90.84mm, with a bore size wear allowance of 0.1mm, giving a maximum bore size of 91.44mm. Max capacity not to exceed 2025 CCs. Stroke 77.050 max – 76.850 min mm.
- b) A standard crankshaft shall be used. Spot machining to achieve balance is permitted. Tuftriding, Parkerizing, shot peening, shot blasting and polishing are permitted. Minimum weight is 12.47Kgs (27.5lbs). Standard oversize and undersize bearings are permitted. This does not allow reducing the bearing surface area by reducing the width of standard bearings.
- c) The flywheel shall be a standard Ford production item for the 2000cc SOHC 'Pinto' engine. The clutch may be a standard unit or an AP Cover plate assembly CP2511-1 with driven plate CP5351-1. Machining to achieve minimum weight and balance is permitted. Flywheel bolts are free and locating dowels are permitted. A Ford 'Kent' 1600 GT starter ring may be fitted. Minimum weight of flywheel and clutch assembly with cover-plate to flywheel bolts but excluding flywheel to crankshaft bolts and dowels, 13Kgs.
- d) Maximum compression ratio will be controlled as follows: -
 - i) Minimum cylinder head combustion chamber volume 50cc (not including head gasket). Polishing and/or grinding of the cylinder head to achieve only the required combustion chamber volume is permitted.
 - ii) Standard Ford gasket minimum compressed thickness 0.9mm. Minimum diameter of cylinder aperture 92mm.
 - iii) Pistons shall not protrude above the cylinder block surface at TDC.
- e) Pistons must be the standard Ford component for this engine or absolutely identical aftermarket production pistons, unmodified in any way except for balancing as follows: - To achieve balance material may be removed from the internal surfaces at any location below the lowest point of the gudgeon pin. All external surfaces, dimensions and profiles must remain standard for the nominal size of piston being used, with the exception of the top surface of the piston crown which may be subjected to simple machining to achieve balance and the objectives of the above clause regarding compression ratio. Minimum permitted weight of piston complete with rings, gudgeon pin and standard Ford connecting rod with bolts and without bearings = 1255 grams. All 3 piston rings shall be fitted. Compression rings and scraper second rings shall be one-piece single homogeneous material type with conventional plain gaps. Chromium or molybdenum plating of the top ring is optional; oil control rings shall be either single piece twin land type or apex 3 piece (2 rails and an expander).
- f) Connecting rods shall be standard Ford parts. Alternate connecting rod and big end bolt assembly part no. M6200C200 are permitted. ARP big end bolts part no. ARPBE03 are permitted.
- g) Machining is permitted to remove metal from the balancing bosses to achieve balance only. In addition the outside diameter of the small end forging may be machined around to the shank blends only. The rod shank may not be machined. Tuftriding, Parkerizing shot peening, shot blasting, polishing etc. are permitted. It is permitted to radius the area around the big end cap retaining bolts.
- h) Valves shall remain standard. No re-profiling or polishing is permitted. The original 45° seat angle shall be maintained. Maximum face diameter inlet is 42.2mm Maximum face diameter exhaust 36.2mm Maximum valve stem diameter 8.4mm. Overall length, inlet 111.15mm (±0.5mm). Overall length, exhaust 110.55mm (±0.5mm).
- i) It is permissible to reshape inlet and exhaust ports by removal of metal within limits. Addition of material in any form is prohibited. The maximum diameter of inlet port at manifold head face 39.5mm. Maximum dimension of exhaust port at manifold face 35.5mm x 27mm. The distance between the valve centres and the angles of all the valves shall not be altered.
- j) The only permitted camshafts and rockers are the standard Ford production items for the 2000cc SOHC 'Pinto' engine. They shall be fully manufactured and ground by the Ford Motor Co. and have the following Finis codes: Camshaft-1584660 Camshaft/follower kit-5004836. The camshaft and rockers shall remain entirely unmodified. Offset keys are permitted. Vernier pulleys are permitted. It is prohibited to grind from blanks, regrind or re-profile. Tuftriding or Parkerizing is permitted. Maximum valve lift at determined points by camshaft rotation will be established by the use of low rate substitute valve spring (load characteristics 12lbs at 1.417" and 30lbs at 1.000") with zero tappet clearance. Camshaft duration (profile) and Inlet to Exhaust lobe timing interval may be checked against Ford data, initially by the use of a profile gauge and secondly by an appointed specialist, if deemed necessary.
- k) Maximum valve lift against cam angle with zero tappet clearance (lift measured in mms)

Angle	Inlet		Exhaust	
	Opening	Closing	Opening	Closing
0	10.442	10.442	10.442	10.442
5	10.36	10.36	10.36	10.36
10	10.11	10.11	10.11	10.11
15	9.69	9.69	9.69	9.69
20	9.11	9.11	9.11	9.11
30	7.45	7.45	7.45	7.45
40	5.17	5.17	5.17	5.17
45	3.86	3.86	3.86	3.86
50	2.58	2.59	2.58	2.59
60	.81	.86	.81	.86
70	.43	.54	.43	.54
80	.19	.37	.19	.37
90	.01	.20	.01	.20

- l) It is permitted as a means of repair to replace damaged valve seats and cylinder bores by replacement cast iron valve seat inserts and cast iron cylinder liners. Valve guides may be replaced with cast iron or bronze all to standard dimensions. Holes left by the removal of non-standard external oilways shall be mechanically plugged.
- m) Balancing of reciprocating and rotating parts is permitted only by removal of metal from locations so provided by the manufacturer.
- n) Non-standard rocker covers are permitted provided they in no way improve the performance of the engine.
- o) Standard valve spring retainers shall be used and single valve springs only are permitted. Shims are permitted and valve springs are otherwise free.
- p) Gaskets and seals are unrestricted except for cylinder head gasket, carburettor to inlet manifold gasket and inlet manifold to head gasket which must be dimensionally identical and of a similar type to original Ford gaskets for this engine.
- q) Pump, fan and generator drive pulleys are unrestricted. The crank case breather may be altered or removed but all breathers shall discharge into a catch tank. Mechanical tachometer drives may be fitted.
- r) Localised machining of the cylinder block is permitted to allow fitting of a dry sump system.

5.7.2 Modifications Prohibited: Any not specifically permitted in 5.7.1. The addition of material by any means to any component is prohibited. Only

modifications or additions specifically covered by these regulations are permitted. All engine components not covered by these regulations shall remain completely standard and unmodified.

- 5.7.3 Location: Engine must be mounted upright and aligned fore and aft in the chassis.
- 5.7.4 Oil/Water cooling: The lubrication system, external to the engine, is free. Existing standard production oilways, linings or oil grooves may be enlarged or reduced, but no additional ones are permitted. Standard friction surfaces must remain unchanged. Dry sump is permitted, oil coolers are free. A liquid cooling system is mandatory but the radiator is unrestricted. The radiator if housed in or incorporating a cowl air scoop deflector shall comply with body regulations. The water pump must stay in the standard Ford position and be belt driven from the engine crankshaft.
- 5.7.5 Induction System: A single carburettor only will be used on a standard inlet manifold. The carburettor will be a Weber 32/36 DGV 26/27mm venturi. Its origin, being from a 1600 GT Kent or 2000 SOHC 'Pinto' engine. The air cleaner may be removed and a trumpet fitted, and the jets may be changed, both throttles may open together. Cold start devices and diffuser bar may be removed. Internal and external anti-surge pipes may be fitted and seals on emission control carburettors may be removed. No other modifications are permitted. Chokes (Venturi) shall remain standard and no polishing or profiling is permitted. Only the standard inlet manifold shall be used. The ports may be reshaped by the removal of metal as long as the following dimensions are maintained: maximum size at head face = 1.437" (36.5mm), maximum size at carburettor flange = 3.405" (86.5mm) x 1.595" (40.5mm). The carburettor seat face may be machined to horizontal in the fore to aft plane. The diameter of the ports may exceed the above listed dimensions if the casting bore is untouched and in its original state. The water passages in the inlet manifold may be plugged. Holes in the inlet manifold resulting from the removal of emission/vacuum lines shall be plugged.
- 5.7.6 Exhaust systems: Exhaust systems and manifold are unrestricted but must comply with MSA regulations E.12.16.
- 5.7.7 Ignition System: Distributors are unrestricted providing they retain the original drive and location. The distributor is defined as the component which triggers the LT current and distributes the HT current. The ignition timing may only be varied by vacuum and/or mechanical means. A rev limiter is permitted. No engine management system is permitted. Only ignition systems that use only one trigger, inside the distributor or external, to initiate the low-tension current will be permitted. Any system that requires more than one sensor or input to provide another signal/voltage for any electronic/microprocessor control system will not be permitted.
- 5.7.8 Fuel delivery system: Only the standard mechanical fuel pump for the engine is permitted.

5.8 SUSPENSION

All parts shall be of steel or ferrous material with the exception of hubs, hub adapters, hub carriers, uprights, bearings and bushes, bell-cranks, pivot blocks and bushes, spring caps, abutment nuts and anti-roll bar links. Springs, steel only. Shock absorbers may be of steel, ferrous material or aluminium alloy, subject to the provisions of 5.2.

There will be four shock absorbers and steel springs, one per wheel. It is not permitted to control body roll with additional shock absorbers.

5.8.1 Permitted Modifications: None

5.8.2 Prohibited Modifications:

- Titanium is prohibited.
- Chromium plating of any steel suspension part is forbidden.
- Active suspension is prohibited, as is any system that allows control of the main suspension spring rate, damper settings and ride height when the car is moving. However, anti-roll (sway) bars may be capable of manual, mechanical adjustment by the driver when seated in the car.
- Shock absorbers (dampers) may be externally adjustable in bump and adjustable in rebound. Multiple adjustable (more than 2 way) shock absorbers are not permitted.
- The springing medium must not consist solely of bolts located through flexible bushes or mountings.

5.9 TRANSMISSIONS

5.9.1 Permitted Modifications: The gearbox shall include an operable reverse gear capable of being engaged by the driver while normally seated and contain not more than 4 forward gears. The ratios are unrestricted.

5.9.2 Prohibited Modifications: The differential cannot be modified in any way to limit its normal function. Torque biasing, limited slip and lock differentials are prohibited. Excessive shimming of the differential is prohibited. Non-ferrous differential components are prohibited. Electronic assisted gear change mechanisms and electronically controlled differentials are prohibited. The use of automatic and/or sequential gearbox is prohibited.

5.9.3 Transmission & drive ratios: Rear wheel drive only is permitted. Final drive ratio is unrestricted.

5.10 ELECTRICS

5.10.1 Exterior Lighting: At least one brake-light of minimum 21 watts rating (or equivalent) and one rear warning light shall be operable and visible from the rear of the car. The rear warning light shall meet the requirements of MSA regulation Q5. There shall be a minimum gap of 5cm between the brake light and rear warning light, when viewed from the rear of the car.

5.10.2 An onboard battery and driver operated onboard engine self-starter is mandatory.

5.10.3 Generators: Generators are optional.

5.11 BRAKES

- Only one caliper per wheel is permitted.
- A maximum of 4 (four) pistons per caliper are permitted.
- Cooling of the calipers shall be by way of direct radiation of heat, from the caliper surface to the airstream.
- Ducting to provide airflow to the caliper, created by the forward motion of the car is permitted. All other methods of cooling are prohibited.
- The calipers used shall be available to all, and be as shown in the caliper manufacturers' current catalogue.
- No other material than iron or steel is permitted for brake discs.

5.11.1 Permitted Modifications:

- Class A: The main caliper body material may only be of a homogenous material, i.e. iron, steel or aluminium alloy.
- Class A, B and H: Calipers fitted as original equipment to the cars, but no longer listed as a current product and complying to 5.2 of these regulations, are permitted. The onus of proof shall be with the competitor/entrant.

5.11.2 Prohibited Modifications:

- Class B and H - Light alloy brake calipers are prohibited.

5.12 WHEELS/STEERING

5.12.1 Permitted options: Unrestricted apart from 5.12.2 below.

5.12.2 Prohibited options: Rear wheel steering is prohibited.

5.12.3 Construction & materials:

- Steering: Material must be metal, with the exception of bushes, seals gaiters and dust covers

b) Wheels: Material is unrestricted providing it is metal.

5.12.4 Dimensions:

a) Wheels: 13" diameter wheels with front rim width of 6" and rear rim width of 8" are the only wheel sizes permitted

5.13 TYRES

5.13.1 Specifications: Front: 160/515/13. Code N2284 or code 811 (slick) and code 829 (wet), Rear: 200/550/13. Code N 2285 or code 810 (slick) and code 830 (wet). The use of un-cut wets is prohibited. NOTE: The 811 and 810 Yokohama slick tyre has been replaced by the N2284 and N2285 tyre.

5.13.2 Nominated Manufacturers: The only permitted tyres are YOKOHAMA

5.13.3 Proprietary tyre softening compounds and any other similar additive or treatment, designed to improve the performance of the tyre are prohibited. Any competitor found to be in breach of this regulation will be excluded from the championship.

5.14 WEIGHTS

5.14.1 Minimum weight excluding driver 500Kg. No allowance given, for topping-up of fluids.

5.15 FUEL TANK

5.15.1 Types: Up to 31.8ltr (7 gal), unless FT3 Spec when 54.5ltr (12 gal) is the maximum. Fuel cells shall be isolated by means of bulkheads and be vented in case of spillage, leakage, or a failure of the cell that fuel and fumes will not pass into the driver or engine compartment or around any part of the exhaust system. There shall be a liquid tight and fireproof bulkhead separating the fuel tanks from the cockpit. Metal tanks may be used if covered externally with a fireproof coating and are mounted within the main chassis structure.

5.15.2 Locations: Free within MSA regulations.

5.15.3 Fuel: Only petrol of the type on sale to the general public from UK roadside filling stations is permitted. See MSA Regulations section P for limits in petrol. No additives of any description can be mixed with the pump fuel.

5.16 SILENCING

5.16.1 Specification: As per MSA regulations E. 12. 17

5.17 NUMBERS AND CHAMPIONSHIP DECALS

5.17.1 Competition numbers and backgrounds shall be displayed in accordance with the requirements of the Championship Organisers and MSA regulations. The numbers and backgrounds shall be of regulation size with number backgrounds conforming to the following colours: Class A: White with black numbers. Class B: Black with white numbers. Class H: Yellow with black numbers. Black and Yellow backgrounds must be of the exact shade available from the Championship Organisers. SRCC, Yokohama and sponsor decals must be affixed on both sides of the vehicle; failure to comply will render the car ineligible.

5.17.2 Suppliers: Class distinction backgrounds, club and sponsor's decals will be available at each round.

6 APPENDICES

The following Commercial Undertakings are not subject to the Judicial procedures of either the Championship Stewards and/or the MSA/MSc

6.1 Race Organising Clubs & Contacts:

Sports 2000 Racing Car Club

51 London Lane,
Bromley,
Kent
BR1 4HB
Tel: 0208 460 3511 (eves)
Tel: 0207 277 5572 (days)

BRSCC HQ

Homesdale Business Centre
Platt Industrial Estate
Borough Green
Kent
TN15 8JL
Tel: 01732 780100
Fax: 01732 885783

6.2 Commercial Undertakings:

6.2.1 Vehicle Presentation: The presentation of the car is fundamental to the profile of the championship/series its sponsors and its audience. Therefore in considering whether to permit any car to race, and any point during the season, the organisers will regard as paramount the presentation of the car. In taking into account its appearance inherent in which is the standard of its presentation (including interior) they may exclude any car, which they consider may prejudice the reputation of the championship/series, or is otherwise unacceptable. This will include where the car is presented at a race event bearing accident damage sustained at a previous event and which has not been subject to the completion of an acceptable repair. Note: A Double Header can be regarded as one event for the purpose of this regulation.

6.2.2 All competitors will park in a neat and tidy manner only in the areas allocated to them by the Race Organisers and will keep these areas clean and tidy at all times. Any competitor failing to obey the instructions of the Organisers or an Official of the Meeting in these matters, in regard to their location, amount of space utilised or manner, in which it is utilised, may be reported to the Clerk of Course who may impose any penalty considered appropriate.